

PRODUCT DATA SHEET

P2UD Clear Coat is a specially formulated water based poly-urethane acrylic blended emulsion. A coating that is UV stable and designed to be durable and trafficable as a topcoat or sealer.

Coverage:	<ul style="list-style-type: none"> • 20 Liter : 50m² at 400mic • 5 Liter: 12.5m² at 400mic
Drying Time:	<ul style="list-style-type: none"> • Touch Dry: 1 – 2 Hours at ± 25°C • Full Curing: 7 Days at ± 25°C
Cleaning:	<ul style="list-style-type: none"> • Clean water
Regulatory Data:	
Flashpoint:	<ul style="list-style-type: none"> • >90°C
Product Weight:	<ul style="list-style-type: none"> • SP >1
VOC:	<ul style="list-style-type: none"> • Low VOC's <1 %
Characteristics:	<ul style="list-style-type: none"> • Non-Flammable • Water Resistant • UV Stable • Adhesion properties
Safety Precautions & Reactivity:	
Inhalation:	<ul style="list-style-type: none"> • No specific hazards associated with this product
Ingestion:	<ul style="list-style-type: none"> • No specific health warnings noted
Skin Contact:	<ul style="list-style-type: none"> • No harmful effects expected in amount likely to be indigested by accident - consult a Physician immediately
Eye Contact:	<ul style="list-style-type: none"> • Prolonged contact may cause dryness of the skin • May cause temporary eye irritation
Health Warnings:	<ul style="list-style-type: none"> • This product has low toxicity. Only large volumes may have adverse impact on human health
Ecological Information:	<ul style="list-style-type: none"> • Eco Toxicity: Eco Friendly
Persistence & Degradability:	<ul style="list-style-type: none"> • The product is expected to be biodegradable
Environmental Hazards:	<ul style="list-style-type: none"> • Non-environmentally hazardous
Pack size:	<ul style="list-style-type: none"> • 20 Liter and 5 Liter
Shipping Weight:	<ul style="list-style-type: none"> • 20 Kg
Storage:	<ul style="list-style-type: none"> • 9 Months maximum at 25°C (Once opened, use within one month) • Store in cool dry conditions

DISCLAIMER

This data sheet is issued as a guide for use of the product(s) concerned. Whilst SealPro endeavors to ensure that any advice, recommendation, specification or information is accurate and correct, the company cannot – (as SealPro has no direct or continuous control over where and how SealPro products are applied) – accept any liability either directly or indirectly arising from the use of SealPro products, whether or not in accordance with any advice, specification, recommendation or information given by the company. Where other products are to be used in conjunction with this material, the relevant technical data sheets should be consulted to determine total requirements. SealPro has a wealth of technical and practical experience built up over years in the company's pursuit of excellence in building and construction technology.

General Disclaimer

The material and information in these sheets are provided as a guide and without warranties of any kind, either expressed or implied. All warranties, including but not limited to, implied warranties by a representative and fitness for a particular purpose, are disclaimed. In no event shall the Company, nor any of its subsidiaries or affiliates, be liable to any party for any cost or damages, including any direct, indirect, special, incidental, or consequential damages, arising out of the incorrect choice of product and/or method of application.

Intellectual Property

Except as indicated otherwise, all information, text, graphic images, features or functions contained in these Data sheets are the exclusive property of SealPro and may not be copied or distributed, in whole or in part, without the Company's express written consent. However, you may download or print any Data Sheets from the website for personal, non-commercial use, provided you do not remove any copyright notices.

CONFIDENTIAL