



P2UD Clear Coat is a specially formulated water based poly-urethane acrylic blended emulsion. A coating that is UV stable and designed to be durable and trafficable as a topcoat or sealer.

Application Method

- Ensure all surroundings and non-sprayable areas are covered and masked to avoid damage or overspray
- Ensure that the base is dry and free of debris, dust or any objects that might cause non-adhesion to the substrate P2UD Clear Coat is pre-mixed therefore when ready for application open 20 liter bucket and mix at medium speed
- Ensure that the substrate that is about to be sprayed is kept clean and free of debris and dust or any objects that might affect the adhesion or aesthetics of the coating at all times by continuous brushing or usage of compressed air on the immediate area to be sprayed

IF SPRAYED:

- Make use of a low pressure spray gun and compressor applying at 100mic per layer
- Minimum of 4 coats to achieve 400mic
- A 400mic thickness should be maintained for domestic use
- Light industrial and industrial applications require more coats, maintaining the same thickness per layer

IF ROLLED:

- P2UD might entrap air, using the incorrect roller, therefore we recommend using a short bristle roller or sponge roller
- With a roll-on application a minimum of 80mic needs to be achieved. Minimum of 5 layers to achieve 400 mic
- If brushed it is important to apply in one direction to avoid air entrapment
- It is generally accepted that a brush application renders thicker layers therefore the application might be only 3 layers to achieve 300mic (This will have to be assessed on site)
- After curing for at least 24 hours at $\pm 25^{\circ}\text{C}$ it might be necessary to do a "Flush" coat to cover uneven areas

Applications

1. P2UD must be applied to all SealPro flooring systems
2. It can be used as a brick, stone or concrete surface sealer
3. Domestic applications through to industrial applications has different requirements with regards to trafficability and durability hence the application of multiple layers

P2UD is a white milky substance that will dry to a clear finish. **It is a requirement to apply a specially formulated polymer enhanced wax layer and buffing the surface after full curing**